



BG-MVS4X4-4KL

4X4 4K UHD HDMI VIDEO WALL PROCESSOR/
SEAMLESS MATRIX SWITCHER

The BG-MVS4X4-4KL 4K60 4:4:4 HDMI matrix is a versatile high-speed matrix switcher and video wall processor with multiple applications. This system can be configured for two different output modes, serving as a 4x4 seamless matrix switcher or as a 2x2, 4x1, or 1x4 video wall solution, among other possibilities.

Additionally, it is equipped with a web browser interface module for convenient control and configuration when used either as a standalone device or in conjunction with a third-party control system. Control options include front-panel push buttons, an IR remote control, RS-232 interface, and TCP/IP connectivity.



FEATURES



COMPLIANT

HDMI 2.0b, HDCP 2.2 and HDCP 1.4



2 OPERATIONAL MODES

4x4 Matrix (seamless switch), Video wall (2x2, 4x1 or 1x4 etc configuration)



AUDIO FORMATS

Support LPCM, DD, DD+, DTS, Dolby TrueHD, DTS HD-master pass-through



ADVANCED EDID MANAGEMENT

Seamless communication between sources and displays



WEB INTERFACE MODULE

For control and configuration of Matrix



CONTROL OPTIONS

Control via front panel, IR, RS-232, and TCP/IP



TECH SPECIFICATIONS

Technical

HDMI Compliance	HDMI 2.0b
HDCP Compliance	HDCP 2.2/1.4
Video Bandwidth	594MHz/18Gbps
Video Resolution	Input: VGA-WUXGA (up to 1920x1200@60Hz), 480i-4K (3840x2160@60Hz 4:4:4, 4096x2160@60Hz 4:4:4) Output: 4096x2160p60, 4096x2160p50, 3840x2160p60, 3840x2160p50, 3840x2160p30, 1920x1080p60, 1920x1080p50, 1920x1080i60, 1920x1080i50, 1920x1200p60rb, 1360x768p60, 1280x800p60, 1280x720p60, 1280x720p50, 1024x768p60, auto
Color Space	RGB, YCbCr 4:4:4/4:2:2, YUV 4:2:0
Color Depth	8/10/12-bit
IR Level	12Vp-p
IR Frequency	38KHz
HDMI Audio Formats	LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio

Connection

Inputs	4 x HDMI Type A [19-pin female]
Outputs	4 x HDMI Type A [19-pin female]
Control	1 x RS-232 [3pin-3.81mm phoenix connector] 1 x TCP/IP [RJ45] 1 x IR EXT [3.5mm Stereo Mini-jack]

Mechanical

Housing	Metal Enclosure
Color	Black
Dimensions	11in (W) x 6.5in (D) x 1.2in (H) [270mm (W) x 166mm (D) x 30mm (H)]
Weight	2.6 lbs [1165g]
Power Supply	Input: AC 100 - 240V 50/60Hz Output: DC 12V/2.5A (US/EU standard, CE/FCC/UL certified)
Power Consumption	19.56W (Max)
Operating Temperature	32°F ~ 104°F / 0°C ~ 40°C
Storage Temperature	-4°F ~ 140°F / -20°C ~ 60°C
Relative Humidity	20~90% RH (non-condensing)



Limited Product Warranty Terms

Pro Line: 5-year warranty from the date of purchase for AV/Broadcasting products bought on or after August 1, 2024.

Essential Line: 3-year warranty from the date of purchase for AV/Broadcasting products bought on or after August 1, 2024.

Cables: Lifetime Limited Product Warranty.

For complete warranty information, please visit bzbgear.com/warranty.
For questions, please call 1.888.499.9906 or email support@bzbgear.com.

Pro Line Products
5-YEAR WARRANTY
Essential Line Products
3-YEAR WARRANTY
Cables Products
LIFETIME WARRANTY

